Technical information Productnumber : 86G20-50



Product description

High-quality aluminum ramp with curved construction, set of 2 pieces. A curved ramp is widely used for low machines and vehicles. A curved construction ensures that there is no 'deep' angle between the highest point of the ramp and the tail lift / elevation. Easy to move due to the light weight, 4.3 kg each. The anti-slip profile prevents slipping.

Maximum load capacity 450 kg. Ideal angle 27 degrees. Ideal trailer height 68 cm. The load capacity depends on various factors and decreases if:

- the drive-on height of the ramp decreases.
- the axle distance is less than 1250 mm.
- the road contact is less than 100 x 150 mm.
- the weight distribution is different than 2/3 on one axle and 1/3 on the other axle.
- drive-up speeds are above 5 km/h.
- there are vibrations when accelerating or braking abruptly.

The ramps must be fully raised with the flat part attached to the bottom of the trailer so that it cannot slide. When calculating the load capacity, the dynamic load has been taken into account and the safety factor 2 has been used with a weight of more than 500 kg. Calculate the weight as follows; total weight of the vehicle + fuel (1 liter is 1 kg) + weight of 1 person + weight of accessories.

* not suitable for tracked vehicles!

Specifications

Article arrangement: New Version: aluminium 200 cm (pair) Top: driving area of anti slip profile Width (mm): 200 Loading capacity (kg): 450 Options: NOT suitable for caterpillar Batch (items): 2 Min Height (mm): 500 EAN Code (Gtin) 8719424025613 Type: access ramp curved Material: aluminium Length (mm): 1994 Height (mm): 50 Weight (kg) 4.3 Type number: 86G Drive width: 200 Max Height (mm): 681














Technical information Productnumber: 86G20-50







KRUIZINGA.FR[®] Stockage et ressources de transport

