

Image not found or type unknown.



## Technical information

**Productnumber : 75.184.792.103K**



### Product description

for more information see manual.

Applications: For medium-heavy transport on flat floors. Low rolling resistance. Relatively insensitive to notches and very wear-resistant. Non-marking tyre, quiet running, hygienic.

Suitable surface: Hard and flat such as tiles, cement and coatings.

Suitable environment: Dry and not permanently damp. With alcohol, glycol and many acids, bases and chemicals.

### Specifications

Article arrangement: New

Version: Ø 100 mm

Top: base plate 105x85 mm

Bolt hole: Ø 9 mm

Surface treatment: galvanized

Width (mm): 35

Loading capacity (kg): 200

Wheel bearing: roller bearing

EAN Code (Gtin) 8719424014280

Type: castor wheel with brake

Material: polyurethane rolling surface

Hole centres: 80x60 mm

Colour: colorless

Length (mm): 100

Height (mm): 128

Weight (kg) 1

Type number: 758479

Scan the QR code for more information



**KRUIZINGA.NL®**  
Opslag- en transportmiddelen

**KRUIZINGA.DE®**  
Lager- und Transportmittel

**KRUIZINGA.FR®**  
Stockage et ressources de transport

**KRUIZINGA.COM®**  
Material handling equipment